Speedpacer 4568S / C



SPEED DISPLAYS TRAFFIC DETECTION

Radar. Detection. Software.

Features

- Dot matrix display in XXL size! For speed values and smileys in **45 cm diameter!**
- Displays speed and pictures in AMBER (SP4568S) or RED, YELLOW and GREEN (SP4568C)
- Adjustable: Flashes if speed threshold is exceeded
- Individual bitmaps can be uploaded such as text messages, smiling/frowning faces, speed limits, logos or any other symbols
- Adjustable minimum/maximum speed threshold
- Time controlled activation
- Automatic brightness regulation
- High contrast due to unique display construction
- Large front plate for custom, digitally printed designs
- Robust Lexan front window with anti-glare coating
- Data collection for more than 200.000 records
- Bluetooth for display configuration
- Measurement of the supply voltage
- Deep discharge protection for batteries
- Easy one-man installation
- User friendly control software for Android and Windows
- Unique value for money



Highlights

It is a fact that radar-driven speed displays slow down traffic permanently.

This positive effect can be attributed to the display's ability to alert drivers with responsive messages wherever the device is deployed (school zones, Kindergarten, zebra crossings or on busy roads in residential areas).

The Speedpacer 4568S and 4568C are large dotmatrix displays that suit perfectly for showing speeds driven as well as individual images and text messages. The device can be adapted to any requirements: Customized front plate designs as well as custom images, that can be created within minutes.

Both speed displays offer speed and time triggered images (such as smileys) and short text messages. As an example the devices are able to show different images during school time and the rest of the day.

All these features are put into a compact and extremely smart powder coated aluminium enclosure.



Android is a trademark of Google Inc., Windows is a trademark of Microsoft Inc. Bluetooth is a trademark of Bluetooth SIG

Electrical Data

Display

Input Voltage	12V	Resolution	32 x 48 Pixel
Power Consumption	Low Power Design!	Pixel Grid	14 mm
Standby (Radar on, LEDs of	ff) < 0,2W (!)	Display Area	47 x 69 cm
Display active (speed valu	e) 6W	Reading Distance	approx. 250 m
Peak (all LEDs active)	30W	Readability	Unique contrast due to Special Design
		Update Rate	approx. 1 sec, adjustable
Radar Sensor		Brightness Regulation	Automatically
Operating Frequency	K-Band (24 GHz)	Bitmap Memory	250 Pictures
Transmitting Power	5 mW	Markenia Data	
Certification	FCC, IC, CE approved	Mechanical Data	
Operating Speed	2 199 km/h or	Dimensions	116 x 84 x 4 cm
Detection Range	2 150 mph min. 100 m, avg. 200 m	Weight	17 kg
Accuracy	Truck avg. 300 m ± 3 %	Enclosure	Powder Coated Aluminium
LEDs	_ 5 / 0	Front Plate Sheeting	Customized Digital Print, Highly Reflective yellow or black with red/white border
Brand	High-Performance Osram LEDs "Black Series"	Protection Degree	IP67
Color	Yellow 590 nm (4568S) Red, Green and mixed	Front Window	Lexan, Anti-Glare Coated
	color Yellow (4568C)	Operating Temperature	-25°C to 60°C
Life Span	Long Lifetime and Reliability		
Radiation Angle	30° Lense		
Viewing Angle	> 120°		

Scope of Delivery

• Speed Display Speedpacer 4568S or 4568C

- Software: BT-Comm/GRS/Android App
- Pole Brackets (60 or 76 mm)
- Power supply Cable 12V
- Optional: Variable Pole Clamps
- Optional: Batteries and Solar Power Supply
- Optional: Remote Control Unit RC1



© 2016-10 Sierzega Elektronik GmbH. All rights reserved. Specifications included in this datasheet are subject to change without notice. Valentinstraße 11 - A-4062 Thening - Email: office@sierzega.com - Phone: +43 7221 64 114 0



Sierzega is TÜV Austria EN ISO 9001 certified. The company develops, produces and delivers high-performance radar systems like radar controlled LED displays and traffic detection systems.

